

Silicone rubber cable
 TOPE INT'L CO., LIMITED
 Email: sales@topeintl.com, Tel: +86 (755) 8170 8035

Commodity Code	Model	Rated Voltage(V)	Working Temperature	Wire Gauge(AWG)	Conduct Material	Conductor Structure: pcs Diameter mm	Nominal Cross Section (mm2)	Outside diameter (mm)	Outside Diameter Tolerance	Mean Outside Diameter mm	Insulating Material	Insulation Thickness mm	Pleath Thick mm	Conductor DC Resistance at 20 ° C Ω/km	Package Length m
S5637	AGR-TR	600	-60~+200°C	18	Tinned copper stranded wire	210×0.07				2.4	Silicone rubber	.6		23.2	305
S5638	AGR-TR	600	-60~+200°C	18	Tinned copper stranded wire	384×0.05				2.4	Silicone rubber	.6		23.2	305
S5639	AGR-TR	600	-60~+200°C	16	Tinned copper stranded wire	353×0.07				3.06	Silicone rubber	.76		14.6	305
S5640	AGR-TR	600	-60~+200°C	15	Tinned copper stranded wire	427×0.07				3.3	Silicone rubber	.76		11.3	305
S5641	AGR-TR	600	-60~+200°C	14	Tinned copper stranded wire	530×0.07				3.5	Silicone rubber	.76		8.96	305
S5642	AGR-TR	600	-60~+200°C	13	Tinned copper stranded wire	653×0.07				4	Silicone rubber	.76		7.1	305
S5643	AGR-TR	600	-60~+200°C	12	Tinned copper stranded wire	855×0.07				4.5	Silicone rubber	.76		5.64	100
S5644	AGR-TR	600	-60~+200°C	11	Tinned copper stranded wire	1080×0.07				5.5	Silicone rubber	1.14		4.48	100
S5645	AGR-TR	600	-60~+200°C	10	Tinned copper stranded wire	1050×0.08				6	Silicone rubber	1.14		3.546	100
S5646	AGR-TR	600	-60~+200°C	10	Tinned copper stranded wire	1368×0.07				6	Silicone rubber	1.14		3.546	100
S5647	AGR-TR	600	-60~+200°C	8	Tinned copper stranded wire	2160×0.07				7.2	Silicone rubber	1.52		2.23	100
S5648	AGR-TR	600	-60~+200°C	7	Tinned copper stranded wire	2701×0.07				8	Silicone rubber	1.52		1.768	100
S5649	AGR-TR	600	-60~+200°C	6	Tinned copper stranded wire	3420×0.07				8.5	Silicone rubber	1.52		1.403	100
S5650	AGR-TR	600	-60~+200°C	5	Tinned copper stranded wire	4440×0.07				9.8	Silicone rubber	2		1.113	100
S5651	AGR-TR	600	-60~+200°C	3	Tinned copper stranded wire	3400×0.10				11.4	Silicone rubber	2		.6996	100
S5652	AGR-TR	600	-60~+200°C	2	Tinned copper stranded wire	4522×0.10				12.6	Silicone rubber	2		.5548	100
S5631	AGR-TR	300	-60~+200°C	30	Tinned copper stranded wire	14×0.07				1.3	Silicone rubber	.45		381	305
S5632	AGR-TR	300	-60~+200°C	28	Tinned copper stranded wire	21×0.07				1.3	Silicone rubber	.45		239	305

S5633	AGR-TR	300	-60~ +200°C	26	Tinned copper stranded wire	32×0.07				1.5	Silicone rubber	.5		150	305
S5634	AGR-TR	300	-60~ +200°C	24	Tinned copper stranded wire	52×0.07				1.6	Silicone rubber	.5		94.2	305
S5635	AGR-TR	300	-60~ +200°C	22	Tinned copper stranded wire	84×0.07				1.8	Silicone rubber	.5		59.4	305
S5636	AGR-TR	300	-60~ +200°C	20	Tinned copper stranded wire	140×0.07				2.1	Silicone rubber	.5		36.7	305
S5653	GBB	500	-60~ +200°C		Tinned copper stranded wire	12 × 0.15	.2	0.6		1.8	Silicone rubber	.5	.15	95	200
S5654	GBB	500	-60~ +200°C		Tinned copper stranded wire	16 × 0.15	.3	0.7		2	Silicone rubber	.5	.15	71.2	200
S5655	GBB	500	-60~ +200°C		Tinned copper stranded wire	23 × 0.15	.4	0.85		2.2	Silicone rubber	.5	.15	49.6	200
S5656	GBB	500	-60~ +200°C		Tinned copper stranded wire	28 × 0.15	.5	0.9		2.2	Silicone rubber	.5	.15	40.1	200
S5657	GBB	500	-60~ +200°C		Tinned copper stranded wire	42 × 0.15	.75	1.15		2.5	Silicone rubber	.5	.15	26.7	200
S5658	GBB	500	-60~ +200°C		Tinned copper stranded wire	32 × 0.20	1	1.3		2.7	Silicone rubber	.5	.15	20	200
S5659	GBB	500	-60~ +200°C		Tinned copper stranded wire	40 × 0.20	1.2	1.5		2.8	Silicone rubber	.5	.15	15.9	200
S5660	GBB	500	-60~ +200°C		Tinned copper stranded wire	48 × 0.20	1.5	1.6		3	Silicone rubber	.55	.15	13.7	200
S5661	GBB	500	-60~ +200°C		Tinned copper stranded wire	40 × 0.25	2	1.85		3.4	Silicone rubber	.6	.15	9.9	100
S5662	GBB	500	-60~ +200°C		Tinned copper stranded wire	49 × 0.25	2.5	2.1		3.7	Silicone rubber	.65	.15	8.21	100
S5663	GBB	500	-60~ +200°C		Tinned copper stranded wire	43×0.30	3	2.4		4	Silicone rubber	.65	.15	6.63	100
S5664	GBB	500	-60~ +200°C		Tinned copper stranded wire	50×0.30	3.5	2.7		4.3	Silicone rubber	.65	.15	5.64	100
S5665	GBB	500	-60~ +200°C		Tinned copper stranded wire	56 × 0.30	4	2.8		4.4	Silicone rubber	.65	.2	5.09	100
S5666	GBB	500	-60~ +200°C		Tinned copper stranded wire	77×0.30	5.5	3.4		5.4	Silicone rubber	.7	.2	3.55	100
S5667	GBB	500	-60~ +200°C		Tinned copper stranded wire	84 × 0.30	6	3.6		5.4	Silicone rubber	.7	.2	3.39	100
S5668	GBB	500	-60~ +200°C		Tinned copper stranded wire	63×0.40	8	4.2		6.4	Silicone rubber	.8	.2	2.55	100
S5669	GBB	500	-60~ +200°C		Tinned copper stranded wire	84 × 0.40	10	4.6		6.8	Silicone rubber	.8	.2	1.95	100

S5670	GBB	500	-60~ +200°C		Tinned copper stranded wire	95×0.40	12	5.2		7.8	Silicone rubber	1	.25	1.75	100
S5671	GBB	500	-60~ +200°C		Tinned copper stranded wire	112×0.40	14	5.6		8.5	Silicone rubber	1.2	.25	1.46	100
S5672	GBB	500	-60~ +200°C		Tinned copper stranded wire	126 × 0.40	16	5.8		8.9	Silicone rubber	1.2	.25	1.24	100
S5673	GBB	500	-60~ +200°C		Tinned copper stranded wire	196 × 0.40	25	7.6		10.5	Silicone rubber	1.2	.25	.795	100
S5674	GBB	500	-60~ +200°C		Tinned copper stranded wire	238×0.40	30	8.4		12.5	Silicone rubber	1.8	.25	.68	100
S5675	GBB	500	-60~ +200°C		Tinned copper stranded wire	494 × 0.30	35	8.8		13	Silicone rubber	1.8	.25	.565	100
S5676	GBB	500	-60~ +200°C		Tinned copper stranded wire	396 × 0.40	50	10.6		14.8	Silicone rubber	1.8	.3	.393	100
S5677	GBB	500	-60~ +200°C		Tinned copper stranded wire	551 × 0.40	70	12.8		17	Silicone rubber	1.8	.3	.277	100
S5678	GBB	500	-60~ +200°C		Tinned copper stranded wire	760 × 0.40	95	14.8		19.6	Silicone rubber	2.2	.3	.21	100
S5679	GBB	500	-60~ +200°C		Tinned copper stranded wire	608 × 0.50	120	16.5		21	Silicone rubber	2.2	.35	.164	100
S5680	GBB	500	-60~ +200°C		Tinned copper stranded wire	756 × 0.50	150	18.2		23.1	Silicone rubber	2.2	.35	.132	100
S5681	GBB	500	-60~ +200°C		Tinned copper stranded wire	925 × 0.50	185	20		25.6	Silicone rubber	2.4	.4	.108	100
S5682	GBB	500	-60~ +200°C		Tinned copper stranded wire	1221 × 0.50	240	23		28.6	Silicone rubber	2.4	.4	.0817	100
S5683	GBB	500	-60~ +200°C		Tinned copper stranded wire	1517 × 0.50	300	26		32.4	Silicone rubber	2.8	.4	.0654	100
S5792	UL3071	600	-60~ +200°C	14	Solid core or stranded tinned copper wire	40 × 0.26		1.9		3.76	Silicone rubber	.78	.15	8.96	305
S5793	UL3071	600	-60~ +200°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		3.36	Silicone rubber	.78	.15	14.6	305
S5794	UL3071	600	-60~ +200°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.34		3.2	Silicone rubber	.78	.15	18.3	305
S5795	UL3071	600	-60~ +200°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		3.06	Silicone rubber	.78	.15	23.2	305
S5796	UL3074	600	-60~ +200°C	12	Solid core or stranded tinned copper wire	49 × 0.30		2.7		4.56	Silicone rubber	.78	.15	5.46	305
S5797	UL3075	600	-60~ +200°C	10	Solid core or stranded tinned copper wire	77 × 0.30		3.7		6.3	Silicone rubber	1.15	.15	3.546	305

S5798	UL3122	300	-60~ +200°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		2.58	Silicone rubber	.39	.15	14.6	305
S5799	UL3122	300	-60~ +200°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.34		2.42	Silicone rubber	.39	.15	18.3	305
S5800	UL3122	300	-60~ +200°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		2.28	Silicone rubber	.39	.15	23.2	305
S5801	UL3122	300	-60~ +200°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		2.04	Silicone rubber	.39	.15	36.7	305
S5802	UL3122	300	-60~ +200°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		1.86	Silicone rubber	.39	.15	59.4	610
S5803	UL3122	300	-60~ +200°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		1.68	Silicone rubber	.39	.15	94.2	610
S5804	UL3122	300	-60~ +200°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		1.56	Silicone rubber	.39	.15	150	610
S5814	UL3135	600	-60~ +200°C	10	Solid core or stranded tinned copper wire	77 × 0.30				5.1	Silicone rubber	.78		3.546	305
S5815	UL3135	600	-60~ +200°C	12	Solid core or stranded tinned copper wire	49 × 0.30		2.7		4.26	Silicone rubber	.78		5.64	305
S5816	UL3135	600	-60~ +200°C	14	Solid core or stranded tinned copper wire	40 × 0.26		1.9		3.46	Silicone rubber	.78		8.96	305
S5817	UL3135	600	-60~ +200°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		3.06	Silicone rubber	.78		14.6	305
S5818	UL3135	600	-60~ +200°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.34		2.9	Silicone rubber	.78		18.3	305
S5819	UL3135	600	-60~ +200°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		2.76	Silicone rubber	.78		23.2	305
S5820	UL3135	600	-60~ +200°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		2.52	Silicone rubber	.78		36.7	305
S5821	UL3135	600	-60~ +200°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		2.34	Silicone rubber	.78		59.4	610
S5822	UL3135	600	-60~ +200°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		2.16	Silicone rubber	.78		94.2	610
S5823	UL3135	600	-60~ +200°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		2.04	Silicone rubber	.78		150	610

S5824	UL3135	600	-60~ +200°C	28	Solid core or stranded tinned copper wire	7 × 0.12			1.92	Silicone rubber	.78		239	610
S5825	UL3135	600	-60~ +200°C	30	Solid core or stranded tinned copper wire	7 × 0.10			1.86	Silicone rubber	.78		381	610
S5836	UL3513	600	-55~ +200°C		Tinned copper stranded wire					Silicone rubber				
S5859	UL3530	600	-60~ +200°C	12	Solid core or stranded tinned copper wire	49 × 0.30		2.7	4.26	Silicone rubber	.78		5.64	305
S5860	UL3530	600	-60~ +200°C	14	Solid core or stranded tinned copper wire	40 × 0.30		1.9	3.46	Silicone rubber	.78		8.96	305
S5861	UL3530	600	-60~ +200°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5	3.06	Silicone rubber	.78		14.6	305
S5862	UL3530	600	-60~ +200°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.34	2.86	Silicone rubber	.78		18.3	305
S5863	UL3530	600	-60~ +200°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2	2.76	Silicone rubber	.78		23.2	305
S5864	UL3530	600	-60~ +200°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96	2.52	Silicone rubber	.78		36.7	305
S5865	UL3530	600	-60~ +200°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78	2.34	Silicone rubber	.78		59.4	610
S5866	UL3530	600	-60~ +200°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6	2.16	Silicone rubber	.78		94.2	610
S5867	UL3530	600	-60~ +200°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48	2.04	Silicone rubber	.78		150	610
S5868	UL3530	600	-60~ +200°C	28	Solid core or stranded tinned copper wire	7 × 0.12			1.92	Silicone rubber	.78		239	610
S5869	UL3530	600	-60~ +200°C	30	Solid core or stranded tinned copper wire	7 × 0.10			1.86	Silicone rubber	.78		381	610
S5870	UL3605	600	-60~ +200°C	20	Tinned copper stranded wire	16×0.20			2.8		.76	.15		305
S5871	UL3605	600	-60~ +200°C	18	Tinned copper stranded wire	7×0.40			3.06		.76	.15		305
S5872	UL3605	600	-60~ +200°C	17	Tinned copper stranded wire	32×0.20			3.2		.76	.15		305
S5873	UL3605	600	-60~ +200°C	16	Tinned copper stranded wire	7×0.50			3.3		.76	.15		305

S5874	UL3605	600	-60~ +200°C	14	Tinned copper stranded wire	40×0.26				3.8		.76	.15		305
S5875	UL3605	600	-60~ +200°C	12	Tinned copper stranded wire	49×0.30				4.6		.76	.15		100
S5876	UL3605	600	-60~ +200°C	11	Tinned copper stranded wire	56×0.30				4.7		.76	.2		100
S5877	UL3605	600	-60~ +200°C	10	Tinned copper stranded wire	77×0.30				5.4		.76	.2		100
S5878	UL3605	600	-60~ +200°C	8	Tinned copper stranded wire	66×0.40				7		1.15	.2		100
S5879	UL3605	600	-60~ +200°C	7	Tinned copper stranded wire	84×0.40				8.1		1.52	.2		100
S5880	UL3605	600	-60~ +200°C	5	Tinned copper stranded wire	133×0.40				9.5		1.52	.2		100
S5881	UL3605	600	-60~ +200°C	3	Tinned copper stranded wire	212×0.40				11.2		1.52	.2		100
S5882	UL3605	600	-60~ +200°C	2	Tinned copper stranded wire	266×0.40				12.5		1.52	.3		100
S5883	UL3605	600	-60~ +200°C	1×0	Tinned copper stranded wire	426×0.40				15.5		2.03	.3		100
S5884	UL3605	600	-60~ +200°C	2×0	Tinned copper stranded wire	350×0.50				17		2.03	.3		100
S5615	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	12×0.10	.1	0.4		1.3	Silicone rubber	.45		188	500
S5616	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	39×0.07	.15	0.5		1.4	Silicone rubber	.45		136	500
S5617	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	12×0.15	.2	0.5		1.8	Silicone rubber	.65		95	500
S5618	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	16×0.15	.3	0.7		1.85	Silicone rubber	.6		71.2	200
S5619	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	23×0.15	.4	0.8		1.9	Silicone rubber	.5		49.6	200
S5620	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	28×0.15	.5	1		2.2	Silicone rubber	.6		40.1	200
S5621	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	42×0.15	.75	1.2		2.6	Silicone rubber	.7		26.7	200
S5622	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	32×0.20	1	1.3		2.8	Silicone rubber	.75		20	200

S5623	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	48×0.20	1.5	1.6		3.1	Silicone rubber	.75		13.7	100
S5624	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	40×0.25	2			3.4	Silicone rubber	.85		9.9	100
S5625	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	49×0.25	2.5	2		3.7	Silicone rubber	.85		8.21	100
S5626	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	56×0.30	4	2.9		4.3	Silicone rubber	.7		5.09	100
S5627	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	84×0.30	6	3.6		5.2	Silicone rubber	.8		3.39	100
S5628	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	84×0.40	10	4.6		6.6	Silicone rubber	1		1.95	100
S5629	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	126×0.40	16	5.8		8.4	Silicone rubber	1.2		1.24	100
S5630	AGR	300/500	-60~ +180°C		Bare copper wire or tinned copper stranded wire	196×0.40	25	7.7		10.4	Silicone rubber	1.4		.795	100
S5703	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		3.3	Silicone rubber	1.2		.0817	
S5704	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		3.6	Silicone rubber	1.2		.0817	
S5705	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		3.7	Silicone rubber	1.2		.0817	
S5706	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		4	Silicone rubber	1.2		.0817	
S5707	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		4.3	Silicone rubber	1.2		.0817	
S5708	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		4.4	Silicone rubber	1.2		.0817	
S5709	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		5.6	Silicone rubber	1.4		.0817	
S5710	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		6.6	Silicone rubber	1.5		.0817	
S5711	JG (1000V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		7.8	Silicone rubber	1.6		.0817	

S5712	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		9	Silicone rubber	1.6		.0817	
S5713	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		11.2	Silicone rubber	1.8		.0817	
S5714	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		12.8	Silicone rubber	2		.0817	
S5715	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		15	Silicone rubber	2.2		.0817	
S5716	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		17.2	Silicone rubber	2.2		.0817	
S5717	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		19.8	Silicone rubber	2.5		.0817	
S5718	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		21.5	Silicone rubber	2.5		.0817	
S5719	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		23.4	Silicone rubber	2.6		.0817	
S5720	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		25.2	Silicone rubber	2.6		.0817	
S5721	JG (1000V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	241	240	242		28.6	Silicone rubber	2.8		.0817	
S5684	JG (500V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	28/0.15	.5	0.9		2.9	Silicone rubber	1		40.1	
S5685	JG (500V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	24/0.20	.75	1.15		3.2	Silicone rubber	1		26.7	
S5686	JG (500V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	32/0.20	1	1.3		3.3	Silicone rubber	1		20	
S5687	JG (500V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	48/0.20	1.5	1.6		3.6	Silicone rubber	1		13.7	
S5688	JG (500V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	40/0.25	2	1.85		3.9	Silicone rubber	1		9.9	
S5689	JG (500V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	49/0.25	2.5	2		4	Silicone rubber	1		8.21	
S5690	JG (500V)	500 (690)、1000(1140)	-60~+180°C		Bare copper wire or tinned copper stranded wire	56/0.30	4	2.8		5	Silicone rubber	1.2		5.09	

S5691	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	84/0.30	6	3.6		6	Silicone rubber	1.2		3.39	
S5692	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	84/0.40	10	4.6		7.4	Silicone rubber	1.4		1.95	
S5693	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	126/0.40	16	5.8		8.6	Silicone rubber	1.4		1.24	
S5694	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	196/0.40	25	7.6		10.8	Silicone rubber	1.6		.795	
S5695	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	494/0.30	35	8.8		12.4	Silicone rubber	1.8		.565	
S5696	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	396/0.40	50	10.6		14.6	Silicone rubber	2		.393	
S5697	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	551/0.40	70	12.8		16.8	Silicone rubber	2		.277	
S5698	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	760/0.40	95	14.8		19.2	Silicone rubber	2.2		.21	
S5699	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	608/0.50	120	16.5		21	Silicone rubber	2.2		.164	
S5700	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	760/0.50	150	18.2		23	Silicone rubber	2.4		.132	
S5701	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	925/0.50	185	20		24.8	Silicone rubber	2.4		.108	
S5702	JG (500V)	500 (690)、 1000(1140)	-60~ +180°C		Bare copper wire or tinned copper stranded wire	241	240	242		28.2	Silicone rubber	2.6		.0817	
S5741	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		5.9	Silicone rubber	2.5		40.1	
S5742	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		6.2	Silicone rubber	2.5		26.7	
S5743	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		6.3	Silicone rubber	2.5		20	
S5744	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		7.2	Silicone rubber	2.8		13.7	
S5745	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		7.5	Silicone rubber	2.8		9.9	

S5746	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		8	Silicone rubber	3		8.21	
S5747	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		8.8	Silicone rubber	3		5.09	
S5748	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		10	Silicone rubber	3.2		3.39	
S5749	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		11	Silicone rubber	3.2		1.95	
S5750	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		12.8	Silicone rubber	3.5		1.24	
S5751	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		14.6	Silicone rubber	3.5		.795	
S5752	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		16.2	Silicone rubber	3.7		.565	
S5753	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		18	Silicone rubber	3.7		.393	
S5754	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		20.6	Silicone rubber	3.9		.277	
S5755	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		22.6	Silicone rubber	3.9		.21	
S5756	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		25	Silicone rubber	4.2		.164	
S5757	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		27.2	Silicone rubber	4.5		.132	
S5758	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		29.6	Silicone rubber	4.8		.108	
S5759	JGG	6000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		33.4	Silicone rubber	5.2		.0817	
S5722	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	28/0.15	.5	0.9		4.9	Silicone rubber	2		40.1	
S5723	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	24/0.20	.75	1.15		5.2	Silicone rubber	2		26.7	
S5724	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	32/0.20	1	1.3		5.3	Silicone rubber	2		20	

S5725	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	48/0.20	1.5	1.6		6	Silicone rubber	2.2		13.7	
S5726	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	40/0.25	2	1.85		6.3	Silicone rubber	2.2		9.9	
S5727	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	49/0.25	2.5	2		6.8	Silicone rubber	2.4		8.21	
S5728	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	56/0.30	4	2.8		7.6	Silicone rubber	2.4		5.09	
S5729	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	84/0.30	6	3.6		8.8	Silicone rubber	2.6		3.39	
S5730	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	84/0.40	10	4.6		9.8	Silicone rubber	2.6		1.95	
S5731	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	126/0.40	16	5.8		11.4	Silicone rubber	2.8		1.24	
S5732	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	196/0.40	25	7.6		13.2	Silicone rubber	2.8		.795	
S5733	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	494/0.30	35	8.8		14.4	Silicone rubber	2.8		.565	
S5734	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	396/0.40	50	10.6		16.6	Silicone rubber	3		.393	
S5735	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	551/0.40	70	12.8		18.8	Silicone rubber	3		.277	
S5736	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	760/0.40	95	14.8		21.2	Silicone rubber	3.2		.21	
S5737	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	608/0.50	120	16.5		23	Silicone rubber	3.2		.164	
S5738	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	760/0.50	150	18.2		25.2	Silicone rubber	3.5		.132	
S5739	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	925/0.50	185	20		27	Silicone rubber	3.5		.108	
S5740	JGG	3000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		30	Silicone rubber	3.5		.0817	
S5760	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		8.1	Silicone rubber	3.6		40.1	

S5761	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		8.4	Silicone rubber	3.6		26.7
S5762	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		8.5	Silicone rubber	3.6		20
S5763	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		9.2	Silicone rubber	3.8		13.7
S5764	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		9.5	Silicone rubber	3.8		9.9
S5765	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		10	Silicone rubber	4		8.21
S5766	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		10.8	Silicone rubber	4		5.09
S5767	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		12	Silicone rubber	4.2		3.39
S5768	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		13	Silicone rubber	4.2		1.95
S5769	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		14.8	Silicone rubber	4.5		1.24
S5770	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		16.6	Silicone rubber	4.5		.795
S5771	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		18.5	Silicone rubber	4.8		.565
S5772	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		20.2	Silicone rubber	4.8		.393
S5773	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		22.8	Silicone rubber	5		.277
S5774	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		24.8	Silicone rubber	5		.21
S5775	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		27.5	Silicone rubber	5.5		.164
S5776	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		29.2	Silicone rubber	5.5		.132
S5777	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		31.5	Silicone rubber	5.7		.108

S5778	JGG	10000	-60~ +180°C		Bare copper wire or tinned copper stranded wire	1221/0.50	240	23		35	Silicone rubber	6		.0817	
S5779	UL3068	300	-60~ +150°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		2.58	Silicone rubber	.39	.15	14.6	305
S5780	UL3068	300	-60~ +150°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.34		2.42	Silicone rubber	.39	.15	18.3	305
S5781	UL3068	300	-60~ +150°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		2.28	Silicone rubber	.39	.15	23.2	305
S5782	UL3068	300	-60~ +150°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		2.04	Silicone rubber	.39	.15	36.7	305
S5783	UL3068	300	-60~ +150°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		1.86	Silicone rubber	.39	.15	59.4	610
S5784	UL3068	300	-60~ +150°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		1.68	Silicone rubber	.39	.15	94.2	610
S5785	UL3068	300	-60~ +150°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		1.56	Silicone rubber	.39	.15	150	610
S5786	UL3068	300	-60~ +150°C	28	Solid core or stranded tinned copper wire	7 × 0.12		0.36		1.14	Silicone rubber	.39	.15	239	610
S5787	UL3068	300	-60~ +150°C	30	Solid core or stranded tinned copper wire	7 × 0.10		0.3		1.08	Silicone rubber	.39	.15	381	610
S5788	UL3069	300	-60~ +150°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		2.82	Silicone rubber	.78	.15	36.7	305
S5789	UL3069	300	-60~ +150°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		2.64	Silicone rubber	.78	.15	59.4	610
S5790	UL3069	300	-60~ +150°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		2.46	Silicone rubber	.78	.15	94.2	610
S5791	UL3069	300	-60~ +150°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		2.34	Silicone rubber	.78	.15	150	610
S5805	UL3132	300	-60~ +150°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		2.28	Silicone rubber	.39		14.6	305
S5806	UL3132	300	-60~ +150°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.34		2.12	Silicone rubber	.39		18.3	305
S5807	UL3132	300	-60~ +150°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		1.98	Silicone rubber	.39		23.2	305

S5808	UL3132	300	-60~ +150°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		1.74	Silicone rubber	.39		36.7	305
S5809	UL3132	300	-60~ +150°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		1.56	Silicone rubber	.39		59.4	610
S5810	UL3132	300	-60~ +150°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		1.38	Silicone rubber	.39		94.2	610
S5811	UL3132	300	-60~ +150°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		1.26	Silicone rubber	.39		150	610
S5812	UL3132	300	-60~ +150°C	28	Solid core or stranded tinned copper wire	7 × 0.12		0.36		1.14	Silicone rubber	.39		239	610
S5813	UL3132	300	-60~ +150°C	30	Solid core or stranded tinned copper wire	7 × 0.10		0.3		1.08	Silicone rubber	.39		381	610
S5826	UL3140	300	-60~ +150°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		4.14	Silicone rubber	1.59		36.7	305
S5827	UL3140	300	-60~ +150°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		3.96	Silicone rubber	1.59		59.4	610
S5828	UL3140	300	-60~ +150°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		3.78	Silicone rubber	1.59		94.2	610
S5829	UL3140	300	-60~ +150°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		3.66	Silicone rubber	1.59		150	610
S5830	UL3142	600	-60~ +150°C	12	Solid core or stranded tinned copper wire	49 × 0.30		2.7		5.88	Silicone rubber	1.59		5.64	305
S5831	UL3142	600	-60~ +150°C	14	Solid core or stranded tinned copper wire	40 × 0.30		1.9		5.08	Silicone rubber	1.59		8.96	305
S5832	UL3142	600	-60~ +150°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		4.68	Silicone rubber	1.59		14.6	305
S5833	UL3142	600	-60~ +150°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.3		4.48	Silicone rubber	1.59		18.3	305
S5834	UL3142	600	-60~ +150°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		4.38	Silicone rubber	1.59		23.2	305
S5835	UL3142	600	-60~ +150°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		4.14	Silicone rubber	1.59		36.7	305
S5837	UL3529	600	-60~ +150°C	12	Solid core or stranded tinned copper wire	49 × 0.30		2.7		4.26	Silicone rubber	.78		5.64	305

S5838	UL3529	600	-60~ +150°C	14	Solid core or stranded tinned copper wire	40 × 0.30		1.9		3.46	Silicone rubber	.78		8.96	305
S5839	UL3529	600	-60~ +150°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		3.06	Silicone rubber	.78		14.6	305
S5840	UL3529	600	-60~ +150°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.3		2.86	Silicone rubber	.78		18.3	305
S5841	UL3529	600	-60~ +150°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		2.76	Silicone rubber	.78		23.2	305
S5842	UL3529	600	-60~ +150°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		2.52	Silicone rubber	.78		36.7	305
S5843	UL3529	600	-60~ +150°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		2.34	Silicone rubber	.78		59.4	610
S5844	UL3529	600	-60~ +150°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		2.16	Silicone rubber	.78		94.2	610
S5845	UL3529	600	-60~ +150°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		2.04	Silicone rubber	.78		150	610
S5846	UL3529	600	-60~ +150°C	28	Solid core or stranded tinned copper wire	7 × 0.12		0.36		1.92	Silicone rubber	.78		239	610
S5847	UL3529	600	-60~ +150°C	30	Solid core or stranded tinned copper wire	7 × 0.10		0.3		1.86	Silicone rubber	.78		381	610
S5848	UL3529	600	-60~ +150°C	12	Solid core or stranded tinned copper wire	49 × 0.30		2.7		4.26	Silicone rubber	.78		5.64	305
S5849	UL3529	600	-60~ +150°C	14	Solid core or stranded tinned copper wire	40 × 0.30		1.9		3.46	Silicone rubber	.78		8.96	305
S5850	UL3529	600	-60~ +150°C	16	Solid core or stranded tinned copper wire	7 × 0.50		1.5		3.06	Silicone rubber	.78		14.6	305
S5851	UL3529	600	-60~ +150°C	17	Solid core or stranded tinned copper wire	32 × 0.20		1.3		2.86	Silicone rubber	.78		18.3	305
S5852	UL3529	600	-60~ +150°C	18	Solid core or stranded tinned copper wire	7 × 0.40		1.2		2.76	Silicone rubber	.78		23.2	305
S5853	UL3529	600	-60~ +150°C	20	Solid core or stranded tinned copper wire	7 × 0.32		0.96		2.52	Silicone rubber	.78		36.7	305
S5854	UL3529	600	-60~ +150°C	22	Solid core or stranded tinned copper wire	7 × 0.26		0.78		2.34	Silicone rubber	.78		59.4	610

S5855	UL3529	600	-60~ +150°C	24	Solid core or stranded tinned copper wire	7 × 0.20		0.6		2.16	Silicone rubber	.78		94.2	610
S5856	UL3529	600	-60~ +150°C	26	Solid core or stranded tinned copper wire	7 × 0.16		0.48		2.04	Silicone rubber	.78		150	610
S5857	UL3529	600	-60~ +150°C	28	Solid core or stranded tinned copper wire	7 × 0.12		0.36		1.92	Silicone rubber	.78		239	610
S5858	UL3529	600	-60~ +150°C	30	Solid core or stranded tinned copper wire	7 × 0.10		0.3		1.86	Silicone rubber	.78		381	610